

TYPICAL WALL
 INTERIOR GYPSUM BOARD
 STEEL STUDS W/BATT INSULATION
 EXTERIOR GYPSUM BOARD
DUPONT™ TYVEK® STUCCOWRAP®
 RIGID INSULATION
 BASE COAT W/ EMBEDDED REINFORCING MESH
 FINISH COAT

USE DUPONT™ STRAIGHTFLASH™ VF
 TO SEAL WINDOW FRAME TO DUPONT™
 TYVEK® STUCCOWRAP®

SEALANT

WINDOW FRAME

SEAL BETWEEN DUPONT™ TYVEK®
 STUCCOWRAP® AND WINDOW FRAME
 USING AN APPROVED SEALANT

EIFS - BRICK MOLD WINDOW JAMB

- SEAL ALL DUPONT™ TYVEK® SEAMS AND REPAIR MINOR HOLES WITH DUPONT™ TYVEK® TAPE.
- FASTEN DUPONT™ TYVEK® WITH APPROVED FASTENERS AND SPACING.
- INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- LOCAL LAWS, ZONING, AND BUILDING CODES VARY AND THEREFORE GOVERN OVER MATERIAL SELECTION AND DETAILING SHOWN ABOVE.



Tyvek.