

Tyvek® versus microporous films

Don't settle for less. Choose Tyvek®

DuPont™ Tyvek® garments have long been the first choice in protection for very good reasons: an excellent balance of protection, durability and comfort. No other garments have provided the valuable balance of attributes offered by Tyvek®.

Tyvek® offers durable, superior protection with a big advantage—it fits. When it comes to hazardous particulates like mold, lead and asbestos, protection and safety come first.

But the best protection doesn't matter if it gets in the way of doing a good job. This is what Tyvek* with its comfort-fit design is all about—the durability and protection you expect in an even more comfortable fit.

Versatile Tyvek® garments are used in a wide range of industries and applications, including remediation and abatement, food processing, general maintenance/operations and spray painting.



Tyvek[®] offers an inherent barrier of protection (magnified view).

Microporous films rely on thin film for barrier.

Protection

Tyvek* is an inherent barrier to particles as small as 1 micron in size. The protection offered by Tyvek* is built into the fabric itself. Protection is throughout the fabric and does not rely on thin films or coatings.



Tyvek° is not abraded. Barrier is not compromised.



Microporous films are easily abraded.

Barrier is compromised.

Durability

Tyvek* is lighter weight than most microporous film products, yet it provides superior abrasion resistance. There are no films or laminates to abrade or wear away. In fact, tests prove that Tyvek* is more than twice as durable as microporous films.



Air bubbles Air flows easily with Tyvek*.



No air bubblesMicroporous films provide minimal
to no air flow.

Comfort

Tyvek® breathes. The inherent barrier of Tyvek® creates a tortuous path for particles while allowing air to pass through easily. Tyvek® is generally six times or more breathable than microporous film fabrics. And that helps reduce the risk of heat stress, so you're more comfortable and more productive.





DuPont Personal Protection Contact Customer Service 1 800 931 3456 (US) 1 844 243 6752 (Canada) safespec.dupont.com personalprotection.dupont.com This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.

© 2023 DuPont. All rights reserved. DuPont", the DuPont Oval Logo, and all trademarks and service marks denoted with TM, SM or " are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. (04/23) DSF23_2301-0163_3-7970