



GYPSUM BOARD

DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (2" ONTO FACE OF WALL)

DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM (USE BACKER ROD AS NECESSARY)

DUPONT™ THRU-WALL FLASHING WITH 1/4" DRIP EDGE

LOOSE-LAID STEEL LINTEL

BACKER ROD AND SEALANT BY OTHERS

WINDOW FRAME

NOTE

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

* DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.



Tyvek.
FLUID APPLIED WB

SCALE: NOT TO SCALE

REVISION DATE: 4/28/10

DRAWING: FA-B-W104h

BUMP OUT WINDOW HEAD - METHOD 1

BRICK VENEER / CMU WALL / FLUID APPLIED FLASHING