



**DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND**  
(2" ONTO FACE OF WALL)

**DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM**  
(USE BACKER ROD AS NECESSARY)

**DUPONT™ THRU-WALL FLASHING WITH 1/4" DRIP EDGE**

LOOSE-LAID STEEL LINTEL

SEALANT BY OTHERS

WINDOW FRAME

**NOTE**  
 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.  
 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.  
 \* DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.

SCALE: NOT TO SCALE  
 REVISION DATE: 4/28/10  
 DRAWING: FA-BX-W202h

**FLANGED WINDOW HEAD - METHOD 1**  
 BRICK VENEER / EXTERIOR INSULATION / STEEL STUD WALL / FLUID APPLIED FLASHING



**Tyvek.**  
 FLUID APPLIED WB