

DuPont™ Styrofoam™ Brand Panelmate™ and Panelmate™ Ultra XPS Foam Insulation

Moisture-Resistant Insulation for Precast Concrete Wall Systems

FEATURES/BENEFITS

Description

DuPont™ Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Extruded Polystyrene (XPS) Foam Insulation* products feature moisture resistance for long-lasting thermal performance in precast concrete sandwich panel applications.

The R-value (RSI)* of Styrofoam™ Brand Panelmate™ Insulation products helps create concrete wall systems that are durable, strong and energy efficient. These products are highly resistant to moisture due to DuPont's distinct extrusion process. Closed-cell, rigid plastic foam is extruded with smooth, high-density skins making Panelmate™ and Panelmate™ Ultra moisture resistant and helping to maintain their thermal value when subjected to the concrete panel manufacturing process.

Styrofoam™ Brand Panelmate™ Ultra is designed specifically for insulated precast concrete panels that require above-average thermal performance. It uses patented carbon black materials in the foam for greater thermal performance over other extruded polystyrene insulations. This enhanced formulation helps the foam to absorb infrared radiation, slowing its transmission through the foam and lowering heat flow.

Ease of Installation

When installed properly, Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Insulation products offer economical long-term thermal performance under the harsh conditions of freeze-thaw cycling, a common phenomenon found in precast concrete panels in cold climates.

Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Insulation boards:

- are available in custom sizes and edge treatments
- are lightweight – easy to handle, cut and install
- feature smooth, high-density skins
- resist moisture and freeze-thaw cycling
- provide economical long-lasting thermal performance
- help create concrete wall systems that are durable, strong and energy efficient

Available Sizes

- Width and length: 2' x 8' (600 mm x 2,400 mm)
- Thickness: Custom sizes and edge treatment available upon request.

Not all products are available in all parts of the country. Other product sizes are available by custom order. Contact a DuPont representative for additional information.

Sustainable Solutions

- Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Insulation are reusable in many applications.
- Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Insulation uses BluEdge™ technology. It is hydrochlorofluorocarbon (HCFC) free with zero ozone depletion potential.
- Contain an average of 20% pre-consumer recycled content certified by UL Environment Inc.

* Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Extruded Polystyrene Foam Insulation is a former product of The Dow Chemical Company.

** R means resistance to heat flow. The higher the R-value or RSI (R-Value Système International), the greater the insulating power.

PROPERTIES

DuPont™ Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Extruded Polystyrene (XPS) Foam Insulation products exhibit the physical properties indicated in Table 1 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-866-583-2583 when additional guidance is required for writing specifications that include this product.

TABLE 1: Physical Properties (U.S.) of Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra XPS Foam Insulation

Property and Test Method	Value	
	Styrofoam™ Brand Panelmate™	Styrofoam™ Brand Panelmate™ Ultra
Thermal Resistance per inch, ASTM C518 @ 75°F (24°C) mean temp., ft ² ·h·°F/Btu (m ² ·°C/W) min., R-value (RSI)	5.0 (0.87)	5.6 (0.97)
Compressive Strength, ASTM D1621, kPa, min.	16 (110)	25 (170)
Water Absorption, ASTM C272, % by volume, max.	0.9	0.7
Water Vapour Permeance, ASTM E96, 1" (25 mm), perms (ng/Pa·s·m ²), max.	1.5 (90)	1.5 (90)
Maximum Use Temperature, °F (°C)	165 (74)	165 (74)
Coefficient of Linear Thermal Expansion, ASTM D696, in/in·°F (mm/m·°C)	3.5 x 10 ⁻⁵ (6.3 x 10 ⁻²)	3.5 x 10 ⁻⁵ (6.3 x 10 ⁻²)
Flexural Strength, ASTM C203, psi (kPa), min.	35 (240)	43 (300)

*R means resistance to heat flow. The higher the R-value or RSI (R-Value Système International), the greater the insulating power.

TESTING

Applicable Standards

ASTM International

- ASTM C518 – Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
- ASTM D1621 – Standard Test Method for Compressive Properties of Rigid Cellular Plastics
- ASTM C203 – Standard Test Methods for Breaking Load and Flexural Properties of Block-Type Thermal Insulation
- ASTM D2842 – Standard Test Method for Water Absorption of Rigid Cellular Plastics
- ASTM E96 – Standard Test Methods for Water Vapour Transmission of Materials
- ASTM D2126 – Standard Test Method for Response of Rigid Cellular Plastics to Thermal and Humid Aging

- CAN/ULC S701
- Standard for Thermal Insulation, Polystyrene Boards and Pipe Covering, Type 2 (Styrofoam™ Brand Panelmate™ Insulation), Type 3 (Styrofoam™ Brand Panelmate™ Ultra Insulation)

Notice

Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Insulation products comply with the following codes:

- CCMC Evaluation Listing 12085-L (Styrofoam™ Brand Panelmate™)
- CCMC Evaluation Listing 11420-L (Styrofoam™ Brand Panelmate™ Ultra)

HANDLING

WARNING: For Professional Use Only – Read and follow the entire Handling section and the Safety Data Sheets (SDSs, formerly MSDSs or Material Safety Data Sheets) carefully before use. The information below is designed to protect the user and allow for safe use and handling of Styrofoam™ Brand products. Follow all applicable federal, state, local and employer regulations.

Precautionary Statements

- DuPont™ Styrofoam™ Brand Panelmate™ and Styrofoam™ Brand Panelmate™ Ultra Extruded Polystyrene (XPS) Foam Insulation products are combustible; protect from high heat sources.
- A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult MSDS, call DuPont at 1-866-583-2583 or contact your local building inspector.
- Dispose of any residual Styrofoam™ Brand product, coated debris, or solvent in accordance with applicable federal, state, and local government regulations.

Supplemental Information

View building.dupont.com or contact a local DuPont representative for more specific installation and handling instructions.

Shelf Life and Storage

When stored outdoors, keep insulation boards tarped or covered to protect from weather and weighted down to prevent boards from being blown around by the wind. Store above standing water.



**For more information visit us at
styrofoam.com/panelmate
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont™ Styrofoam™ Brand Extruded Polystyrene Foam Insulation

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.